

HALF MIRROR LAMPS produce a glare-free reflected light. It is recommended that these lamps be used where direct lighting is not desired.

A19



A21



G25



G40



HALF MIRROR

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
A19												
52170	40A19/SLV/3M/HM/130V/STD	40	E26	130	Silver	3 000	C-9	4.3	108	3.1	78	120
52019	60A19/SLV/3M/HM/130V/STD	60	E26	130	Silver	3 000	C-9	4.3	108	3.1	78	120
52020	100A19/SLV/3M/HM/130V/STD	100	E26	130	Silver	3 000	C-9	4.3	108	3.1	78	120
A21												
52051	100A21/SLV/3M/HM/130V/STD	100	E26	130	Silver	3 000	C-9	5.3	135	3.5	89	120
G16.5												
52159	25G16.5/SLV/3M/HM/E12/120V/STD	25	E12	120	Silver	3 000	C-7A	2.9	73	1.9	47	500
52160	40G16.5/SLV/3M/HM/E12/120V/STD	40	E12	120	Silver	3 000	C-7A	2.9	73	1.9	47	500
G25												
52058	25G25/SLV/3M/HM/130V/STD	25	E26	130	Silver	3 000	C-9	4.5	114	3.0	76	60
61836	40G25/SLV/1.5M/HM/120V	40	E26	120	Silver	1 500	C-9	4.5	114	3.0	76	24
52054	60G25/SLV/3M/HM/130V/STD	60	E26	130	Silver	3 000	C-9	4.5	114	3.0	76	60
G30												
52163	40G30/SLV/3M/HM/130V/STD	40	E26	130	Silver	3 000	C-9	5.3	135	3.6	91	500
51160	60G30/SLV/3M/HM/130V/STD	60	E26	130	Silver	3 000	C-9	5.4	137	3.3	84	100
G40												
14502	60G40/SLV/2.5M/HM/130V	60	E26	130	Silver	2 500	C-9	6.8	172	4.4	111	24
14503	100G40/SLV/2.5M/HM/130V	100	E26	130	Silver	2 500	C-9	6.8	172	4.4	111	24
PS35												
14802	300PS35/SB/IF/MOG 120V	300	E39	120	Silver	5 000	C-9	9.4	239	6.5	165	24

FLASHING LAMPS create fantastic light effects for disco. They are available in 5 different colours and each produce about 60 random flashes a minute.

G25



FLASHING

Order code	Description	Watts	Base	Volts	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL		LCL		Case qty
		(W)		(V)				(lm)	(in.)	(mm)	(in.)	(mm)	
G25													
52203	XFLASH/CL/120V	1	E26	120	Clear	10 000 000 flashes	C-11V	1 040	4.7	118	2.4	61	50
52204	XFLASH/B/120V	1	E26	120	Blue	10 000 000 flashes	C-11V	610	4.7	118	2.4	61	50
52205	XFLASH/G/120V	1	E26	120	Green	10 000 000 flashes	C-9	360	4.7	118	2.4	61	50
52206	XFLASH/R/120V	1	E26	120	Red	10 000 000 flashes	C-9	610	4.7	118	2.4	61	50
52207	XFLASH/Y/120V	1	E26	120	Yellow	10 000 000 flashes	C-9	665	4.7	118	2.4	61	50