according to Regulation (EC) No. 1907/2006

# Honeywell

# Genetron® 410A

000000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Genetron® 410A

SDS-number : 000000009881

Type of product : Mixture

Remarks : SDS according to Art. 31 of Regulation (EC) 1907/2006.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the : Refrigerant

Substance/Mixture

Uses advised against : none

1.3. Details of the supplier of the safety data sheet

Company : Honeywell Fluorine Products Honeywell International, Inc.

Europe B.V. 115 Tabor Road

Stationsplein Zuid-West 961 Morris Plains, NJ 07950-2546

1117 CE Schiphol-Oost USA

Netherlands

Telephone : +32 16 391 211

Telefax

For further information, : PMTEU Product Stewardship: please contact: SafetyDataSheet@Honeywell.com

1.4. Emergency telephone number

Emergency telephone : +1-703-527-3887 (ChemTrec-Transport)

number +1-303-389-1414 (Medical)

Country based Poison

Control Center

: see chapter 15.1

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## REGULATION (EC) No 1272/2008

Gases under pressure Liquefied gas

H280 Contains gas under pressure; may explode if heated.

## 2.2. Label elements

#### REGULATION (EC) No 1272/2008

Page 1 / 13

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Hazard pictograms :

 $\langle \rangle$ 

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may

explode if heated.

Precautionary statements : P260 Do not breathe dust/ fume/ gas/ mist/

vapours/ spray.

P280 Wear protective gloves/ eye protection/

face protection.

P284 In case of inadequate ventilation wear

respiratory protection.

P304 + P340 IF INHALED: Remove victim to fresh air

and keep at rest in a position

comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical

advice/ attention.

P410 + P403 Protect from sunlight. Store in a well-

ventilated place.

### 2.3. Other hazards

Warning! Container under pressure.

# **SECTION 3: Composition/information on ingredients**

## 3.1. Substance

Not applicable

#### 3.2. Mixture

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
Difluoromethane	75-10-5 01-2119471312-47 200-839-4	Flam. Gas 1; H220 Press. Gas ; H280	>= 25 % - < 50 %	1*
Pentafluoroethane	354-33-6 01-2119485636-25 206-557-8	Press. Gas ; H280	>= 25 % - < 50 %	1*

<sup>1\* -</sup> For specific concentration limits see Annexes of 1272/2008

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4

Revision Date 10.05.2017

Supersedes 2

Remaining components of this product are non-hazardous and/or are present at concentrations below reportable limits.

Occupational Exposure Limit(s), if available, are listed in Section 8. For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### General advice:

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

#### Inhalation:

Remove to fresh air. Artificial respiration and/or oxygen may be necessary. Call a physician immediately.

#### Skin contact:

Rapid evaporation of the liquid may cause frostbite. In case of contact with liquid, thaw frosted parts with water, then remove clothing carefully. Wash with plenty of water Consult a physician. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use.

## Eve contact:

Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

#### Ingestion:

Ingestion is unlikely because of the physical properties and is not expected to be hazardous. As this product is a gas, refer to the inhalation section.

## 4.2. Most important symptoms and effects, both acute and delayed

no data available

# 4.3. Indication of any immediate medical attention and special treatment needed

Do not give adrenaline or similar drugs.

See Section 11 for more detailed information on health effects and symptoms.

according to Regulation (EC) No. 1907/2006



## Genetron® 410A

000000009881

Version 3.4 Revision Date 10.05.2017

Supersedes 2

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: The product is not flammable. ASTM D 56-82 ASTM E-681

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

This product is not flammable at ambient temperatures and atmospheric pressure.

However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water courses.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Fire may cause evolution of:

Halogenated compounds

Hydrogen fluoride

Carbon oxides

Carbonyl halides

# 5.3. Advice for firefighters

Wear full protective clothing and self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Immediately contact emergency personnel. Wear personal protective equipment. Unprotected persons must be kept away. Ensure adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

#### 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. The product evapourates readily.

### 6.3. Methods and materials for containment and cleaning up

Ventilate the area.

#### 6.4. Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4

Revision Date 10.05.2017

Supersedes 2

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling:

Open drum carefully as content may be under pressure. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not use in areas without adequate ventilation. Contaminated equipment (brushes, rags) must be cleaned immediately with water.

## 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions:

Store in original container. Keep away from direct sunlight. Keep containers tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

Specific use information:

Restricted to professional users.

For industrial use only.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### **DNEL/ PNEC-Values**

Component	End-use / Impact	Exposure duration	Value	Exposure routes	Remarks
Pentafluoroethane	Workers / Long-term systemic effects		16444 mg/m3	Inhalation	
Pentafluoroethane	Consumers / Long-term systemic effects		1753 mg/m3	Inhalation	
Difluoromethane	Workers / Long-term systemic effects		7035 mg/m3	Inhalation	

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Difluoromethane	Consumers /	750 mg/m3	Inhalation
	Long-term		
	systemic		
	effects		

Component	Environmental compartment / Value	Remarks
Pentafluoroethane	Fresh w ater: 0,1 mg/l	Assessment factor: 1000
Pentafluoroethane	Fresh w ater sediment: 0,6 mg/kg dw	
Difluoromethane	Fresh w ater: 0,142 mg/l	Assessment factor: 1000
Difluoromethane	Fresh water sediment: 0,534 mg/kg dw	

#### 8.2. Exposure controls

## Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, safety shoes EN-ISO 20345.

#### Personal protective equipment

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment.

Self-contained breathing apparatus (EN 133)

Hand protection:

Glove material: Viton (R)

Gloves must be inspected prior to use.

Replace when worn.

Protective gloves against cold

(EN 511)

Remarks: Supplementary note: The specifications are based on information and tests from similar substances by analogy.

Due to varying conditions (e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374.

Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer reccomends to use the chemical protective glove in practice not longer than 50% of the recomended permeation time.

Manufacturer's directions for use should be observed because of great diversity of types . Suitable gloves tested according EN 374 are supplied e.g. from KCL GmbH, D-36124 Eichenzell, Vertrieb@kcl.de

Eye protection:

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Safety glasses with side-shields conforming to EN166

Face-shield

Skin and body protection:

Protective footwear

## **Environmental exposure controls**

Handle in accordance with local environmental regulations and good industrial practices.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Form : Liquefied gas

Colour : colourless

Odour : weak

molecular weight : Not applicable

Boiling point/boiling range : -48,5 °C

Flash point : Not applicable

Lower explosion limit : None

Upper explosion limit : None

Vapour pressure : 14.844 hPa

at 21,1 °C

Vapour pressure : 33.798 hPa

at 54,4 °C

Density : 1,08 g/cm3

at 21,1 °C

pH : neutral

Water solubility : 1,5 g/l

Partition coefficient: n- : log Pow 1,48

octanol/water Medium: Ethane, pentafluoro- (HFC-125)

Partition coefficient: n- : log Pow 0,21

octanol/water Medium: Difluoromethane (HFC-32)

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

## 00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Relative vapour density : 3

(Air = 1.0)

Evaporation rate : > 1

Method: Compared to CCI4.

9.2 Other Information

no additional data available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Stable under normal conditions. Hazardous polymerisation does not occur.

## 10.2. Chemical stability

no data available

#### 10.3. Possibility of hazardous reactions

no data available

### 10.4. Conditions to avoid

Heating will cause pressure rise with risk of bursting

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandes cent material.

#### 10.5. Incompatible materials

oxidizing substances

Possible incompatibility with alkali sensitive materials.

Powdered metals

## 10.6. Hazardous decomposition products

Halogenated compounds Hydrogen fluoride Carbonyl halides Carbon oxides

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute oral toxicity:
Not applicable

according to Regulation (EC) No. 1907/2006

# Honeywell

# Genetron® 410A

00000009881

Version 3.4

Revision Date 10.05.2017

Supersedes 2

Acute dermal toxicity: no data available

Acute inhalation toxicity:

LC50

Species: Rat

Value: > 800000 ppm Exposure time: 4 h

Test substance: Ethane, pentafluoro- (HFC-125)

LC50

Species: Rat

Value: 520000 ppm Exposure time: 4 h

Test substance: Difluoromethane (HFC-32)

Skin irritation: no data available

Eye irritation: no data available

Respiratory or skin sensitisation:

no data available

Repeated dose toxicity:

Species: Rat NOAEL: 20000 ppm

Aspiration hazard: no data available

Other information:

Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. Difluoromethane. (HFC-32): Cardiac sensitisation threshold (dog): 350000 ppm.

Inhalation: May cause cardiac arrhythmia.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Toxicity to fish: no data available

Toxicity to aquatic plants: no data available

\_

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Toxicity to aquatic invertebrates:

no data available

## 12.2. Persistence and degradability

no data available

#### 12.3. Bioaccumulative potential

no data available

## 12.4. Mobility in soil

no data available

# 12.5. Results of PBT and vPvB assessment

no data available

#### 12.6. Other adverse effects

Accumulation in aquatic organisms is unlikely.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## Product:

Offer surplus and non-recyclable solutions to a licensed disposal company. Refer to manufacturer/supplier for information on recovery/recycling.

# Remarks:

To present knowledge of the supplier, this product is not regarded as hazardous waste as defined by EU Directive 91/689/EC.Classification: 14.06.01

# Further information:

Provisions relating to waste:

EC Directive 2006/12/EC; 2008/98/EEC

Regulation No. 1013/2006

For personal protection see section 8.

# SECTION 14: Transport information

ADR/RID

UN Number : 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(PENTAFLUOROETHANE, DIFLUOROMETHANE)

Class : 2

Page 10 / 13

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

## 00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Classification Code : 2A Hazard Identification : 20

Number

ADR/RID-Labels : 2.2 Environmentally hazardous : no

**IATA** 

UN Number : 3163

Description of the goods : Liquefied gas, n.o.s.

(Pentafluoroethane, Difluoromethane)

Class : 2.2 Hazard Labels : 2.2

**IMDG** 

UN Number : 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(PENTAFLUOROETHANE, DIFLUOROMETHANE)

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### **Poison Control Center**

Country	Phone Number
Austria	+4314064343
Belgium	070 245245
Bulgaria	(+)35929154233
Croatia	(+3851)23-48-342
Cyprus	no data available
Czech Republic	+420224919293; +420224915402
Denmark	82121212
Estonia	16662; (+372)6269390
Finland	9471977
France	+33(0)145425959
Greece	no data available
Hungary	(+36-80)201-199
Iceland	5432222
Ireland	+353(1)8092166

Country	Phone Number		
Latvia	+37167042473		
Liechtenstein	no data available		
Lithuania	+370532362052		
Luxembourg	070245245; (+352)80002-5500		
Malta	no data available		
Netherlands	030-2748888		
Norw ay	22591300		
Poland	no data available		
Portugal	808250143		
Romania	no data available		
Slovakia (NTIC)	+421 2 54 774 166		
Slovenia	no data available		
Spain	+34915620420		
Sw eden	112 (begär Giftinformation);+46104566786		

according to Regulation (EC) No. 1907/2006

# Honeywell

# Genetron® 410A

00000009881

Version 3.4

Revision Date 10.05.2017

Supersedes 2

Italy	no data available	
	Berlin : 030/19240	
	Bonn : 0228/19240	
	Erfurt: 0361/730730	
Germany	Freiburg : 0761/19240	
Comany	Göttingen : 0551/19240	
	Homburg : 06841/19240	
	Mainz: 06131/19240	
	Munich: 089/19240	

United Kingdom	no data available		

## Other inventory information

US. Toxic Substances Control Act On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances On the inventory, or in compliance with the inventory

NZIOC - New Zealand On the inventory, or in compliance with the inventory

# 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

Text of H-statements referred to under heading 3

according to Regulation (EC) No. 1907/2006



# Genetron® 410A

## 00000009881

Version 3.4 Revision Date 10.05.2017 Supersedes 2

Difluoromethane : H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode

if heated.

Pentafluoroethane : H280 Contains gas under pressure; may explode

if heated.

#### **Further information**

All directives and regulations refer to amended versions.

Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

#### Abreviations:

EC European Community

CAS Chemical Abstracts Service

DNEL Derived no effect level

PNEC Predicted no effect level

vPvB Very persistent and very biaccumulative substance

PBT Persistent, bioaccmulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.