



S29391

22W/LED/HID/5000K/100-277V/E26
22 watt - LED HID Replacement; 5000K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size		
Length	Width	Depth
8.5 inch	6 inch	6 inch

Optional Accessories

- In-line surge protector [80-929](#)
- Mog to med socket reducer (rated up to 250V) [92-406](#)



S29391

Item Number	Product Line	UPC		Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent	
S29391	Hi-Pro	045923293917		100 - 277	22	50/60Hz	150W	40W	
HID Equivalent	Base	ANSI Base	Lamp Code			Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
100W	Medium	E26	22W/LED/HID/5000K/100-277V/E26			Non-Dimmable	White	7-11/16"	2-3/4"
Initial Lumens	Average Rated Hours		Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack

2950	50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	48
Package Type	CEC Status	RoHS Compliant	UL Classification	Warranty			
Box	Lawful for sale in California	Yes	cULus - Damp Location Rated	5 Year Limited			



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051