

## S29393

45W/LED/HID/5K/100-277V/EX39 45 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
- Wet location rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60HzWorking Voltage AC90-305V

| Minimum Compartment Size |           |           |  |  |  |
|--------------------------|-----------|-----------|--|--|--|
| Length                   | Width     | Depth     |  |  |  |
| 17.3 inch                | 9.25 inch | 9.25 inch |  |  |  |

Optional accessory: In-line surge protector 80-929



S29393

| Item<br>Number | Product<br>Line   | UPC          | Input<br>Voltage       | Watts | Operating<br>Frequency |                    | descent<br>ivalent |                  | rescent<br>uivalent |  |
|----------------|-------------------|--------------|------------------------|-------|------------------------|--------------------|--------------------|------------------|---------------------|--|
| S29393         | Hi-Pro            | 04592329673  | 4 100 - 277            | 45    | 50/60Hz                | 300W               |                    |                  | 65W                 |  |
| HID Equivalen  | t Base            | ANSI<br>Base | Lamp Co                | ode   | Dimmable<br>Dimma      | -,                 | Finish             | MOL In<br>Inches | MOD In<br>Inches    |  |
| 175W           | Mogul<br>Extended | ex39         | 45W/LED/HID<br>277V/E> |       | Non-Dim                | Non-Dimmable White |                    | 10-3/4"          | 3.69"               |  |

| Initial Lumens Average Rated Kelvin Color CRI Beam Spread C | Operating Temperature Pack |
|-------------------------------------------------------------|----------------------------|
|-------------------------------------------------------------|----------------------------|

| 6000         | 50000                            | 5000 Natural Light         | 80+ | 300           | -20C (-4F) to a maxim<br>+65C (+149F) | um of    | 12             |
|--------------|----------------------------------|----------------------------|-----|---------------|---------------------------------------|----------|----------------|
| Package Type | CEC Status                       | DLC ID:                    | Ro  | oHS Compliant | UL Classification                     | Warranty |                |
| Вох          | Lawful for sale in<br>California | PLJ1C8EGNU8T<br>DLC Search |     | Yes           | cULus - Wet Location<br>Rated         | 5 Year   | <u>Limited</u> |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051