## BC2 & BC202

## **High-Flow Activated Carbon Cartridges**





Rainfresh BC2 & BC202 activated carbon filter cartridges are specifically designed for high-flow chlorine removal applications such as R.O. pre-filtration, Point of Entry (POE) filtration, Icemakers etc.

BC2 & BC202 are manufactured by a unique process, which provides dual filtration in a true depth-style configuration. A combination of low-density media in a 4½" (118 mm) outside diameter results in relatively higher permeability enabling both sediment and carbon treatment.

BC2 & BC202 filters exhibit >95% chlorine removal efficiency for 14,000 gallons (53,000L) & 28,000 gal

(106,000L) respectively, when challenged with a 2.0 ppm free-chlorine feed at a continuous flow rate of 3.0 GPM & 6 GPM respectively

#### **FEATURES**

- Made up of premium grade highly purified activated carbon
- Highly effective in reducing chlorine, taste, odours
- 5μ (micron) nominal sediment filtration.
- Large surface area and over 1" bed depth.
- Resistant to media breakdown under normal operating conditions.
- Fine mesh polyolefin external netting for surface integrity and appearance.
- Inner layer of heat-fused synthetic fiber media for preventing carbon bleed-off.
- Low durometer, thermoplastic rubber gasket to insure effective sealing.
- All components approved for food contact use.
- UNIVERSAL FIT Fits Rainfresh and most high flow filter housings

### **SPECIFICATIONS**

| Model | Cartridge<br>Type  | Length<br>(Inch) | O.D<br>(Inch) | I.D<br>(Inch) | Micron<br>Rating | Rated Service<br>Flow | Max Life                  | Max.<br>Operating<br>Temp |
|-------|--------------------|------------------|---------------|---------------|------------------|-----------------------|---------------------------|---------------------------|
| BC2   | Double<br>Open End | 9.75"            | 4 5/8"        | 1"            | 5μ<br>nominal    | 3 GPM<br>(11.3 LPM)   | 14,000 gal or 6<br>months | 160°F<br>(71°C)           |
| BC202 |                    | 19.5"            |               |               |                  | 6 GPM<br>(22.6 LPM)   | 28,000 gal or 6<br>months |                           |

#### **TESTING AND CERTIFICATION**



Component certified to NSF/ANSI 61 and CSA B483.1 for material requirements only for use with Rainfresh BH010 & BH020 filter housings.

# Apr 2012

 Efficient chlorine removal over long life

BENEFITS

- Higher flow rates
- Long Lasting
- Dual Filtration (sediment & carbon)
- Available in 9.75" and 19.5" lengths
- UNIVERSAL FIT<sup>V</sup>

### **ENVIROGARD PRODUCTS LIMITED**

446 Major Mackenzie Drive East, Richmond Hill, ON L4C 1J2 CANADA **Tel**: 905 884 9388 **Toll Free**: 1 800 667 8072 **Fax**: (905) 884 3532

E mail: info@rainfresh.com Web: www.rainfresh.ca

V-Certification does not extend for use with competitive housings.