Sediment Filtration System



Rainfresh FC150 Sediment Filter is a main line filter designed to reduce sediment, particulates, rust, sand, silt etc., giving you clean fresh water throughout the home.

Featuring full \(\frac{4}{7} \) threaded ports, the FC350 system can be installed on \(\frac{4}{7} \) or \(\frac{4}{7} \) copper or PEX pipe, after the water meter or pressure tank, depending on the water supply.

Performance

Reduces

Sediment down to 5µ nominal



Features

1) Easy-open Housing – No Wrench Required!

The FC150 features Rainfresh's unique easy-open filter housing that does not require the use of a filter wrench. Simply grab the sump and turn 1/8th clockwise to open the sump, without using any tools.







2) Built-in Bypass Valve & Pressure Relief

FC150 also features a built-in shut-off and bypass valve. By simply rotating the top valve, the filter can be either by-passed or shut-off with automatic pressure relief

3) Transparent Sump – See your filter working!

The clear transparent sump allows you to see the filter condition without turning the water off.

Installation Notes:

Unit Width (Inch)	Unit Height (Inch)	Unit Depth (Inch)	Connections
4.75"	13.75"	4.75"	3/4" Female NPT

- Connector kit sold separately
- Leave minimum 5 inches of clearance below the unit to allow removal of housing during filter replacement.

Replacement Cartridge: Model CF1.

Replacement Frequency: Once every 4 - 6 months*or when pressure drops

by 10 psi across the filter.

* - cartridge life is directly dependent on water conditions. High chlorine or sediment levels may cause more frequent replacement



Tested & certified by CSA International to NSF/ANSI 61 and to CSA B483.1







Envirogard Products Limited

Web: www.rainfresh.ca