

Location:



SYMMONS® Elm™

Shower Valve System 5500

Specification Submittal



Feature Highlights

- Symmons Shower Valve System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon
- Polished chrome finish

Model Numbers

- ☐ 5500
Shower Valve System with Symmons Temptrol® mixing valve p/n 4000-BODY
- ☐ 5500-TRM
Trim only, mixing valve ordered separately
- ☐ 5500-REB-TRM
Rebuild kit, Trim only, includes TA-10 flow control spindle and TA-4 hot/cold seat
- ☐ 4000-BODY
Symmons Temptrol® mixing valve without trim
- ☐ 4000-X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- ☐ -STN Satin Nickel
- ☐ -SBZ Seasoned Bronze
- Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

- ☐ -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- ☐ -X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n 4000-X-BODY (*option only applies when ordering model 5500*)
- ☐ -CHKS Check Stops: Temptrol® mixing valve includes integral check stops (*Requires integral service stops, suffix -X. Used in installations where a positive shut-off device is used downstream of mixing valve.*)
- ☐ -REV Reverse core: Temptrol® mixing valve with reverse core. (*Requires integral service stops, suffix -X. Used in back-to-back system installations. HOT on the right, COLD on the left*)

Standards / Certifications

ASME A112.18.1-2005 / CSA B125.1-05

Americans with Disabilities Act (ADA) compliant

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions Elm Shower Valve System, 5500

