# **FRIGID**AIRE

# FFAD3533W1

Moderate Humidity 35 Pint Capacity Dehumidifier

#### SIGNATURE FEATURES

#### Easy-to-Clean Washable Filter Capture dust from the air and keep

your dehumidifier working efficiently with our easy-to-clean washable filter.

#### Continuous Drain Option

Skip emptying the water bucket -this unit continuously drains your dehumidifier so that you don't have to lift a finger. AVAILABLE COLORS

#### **Custom Humidity Control** Maximize your comfort with customized control over the amount of humidity in your room.

#### Automatic Shut Off

Unit shuts off automatically when the water bucket is full.

#### MORE EASY-TO-USE FEATURES

Front Loading Bucket with Carrying Handle and Splash Guard

A water bucket is conveniently located in the front of the unit for easy access, while the carry handle and splash guard make emptying your bucket hassle-free.

#### Portable Design

Easily move from room to room with caster wheels and side handles, dehumidifying your room when and where you need it.

Low Temperature Operation This unit is designed to operate at low temperatures down to 41°F.

Multi-Speed Fan

Enjoy more cooling flexibility with three different fan speeds.

#### ENERGY STAR® Certified

Use less energy, reduce your energy usage and ultimately lower your utility bills.

### FFAD3533W1 Moderate Humidity 35 Pint Capacity Dehumidifier

## **FRIGIDAIRE**

#### **General Specifications**

General Specifications	
Shipping Weight (lbs)	43.36
Prop 65 Label	Yes
Refrigerant Type	R410a
Warranty - Parts	1 yr Full
40 HQ Stuffing Quantity	663
Warranty - Labor	1 yr Full
Stack Height	6
Power Type	Electric
Size	N/A
Installation Type	Free-Standing
Collection	
Dimensions	
Depth	12.19″
Width	15.96″
Height	24.25"
Dehumidifier	
Noise Level dB (High)	51
Noise Level dB (Med)	48
Noise Level dB (Low)	45
Air CFM (High)	229
Air CFM (Med)	194
Air CFM (Low)	167
Motor RPM (High)	1160
Motor RPM (Med)	980
Motor RPM (Low)	880
Filter Type	Easy-to-Clean Washable Filter
Container Full Indication	Yes
Digital Humidity Readout	Yes
Fan Speeds - Fan	3
Low Temperature Operation	Yes
Filter Access	Rear of Unit
Filter Check Indicator	Yes
Container Capacity (Pints)	16.9

Watts	380
Plug Type	LCDI 5-15P
Voltage Rating	115
Power Cord Length	6'
Amps	3.6
inctions	
Continuous Drain Operation	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
24-Hour On/Off Timer	Yes
ontrols	
Control Type	Electronic
ertifications & Approvals	
CUL Listed	Yes
ENERGY STAR® Certified	Yes
Energy Efficiency Verification (Canada)	Yes
JL Listed	Yes
STA 6	Yes
erformance	
Dehumidification - Pints per Day	35.23

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca. Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

### FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

FFAD3533W1 ©2017 Electrolux Home Products, Inc.