



## Electronic Flush Valves & Retrofit Kits

Battery RETROFIT KIT with H2Optics® SENSOR for Sloan®/Zurn® Manual or Electronic URINAL Flush Valves for 3/4" top spud - 13" height  
LESS STOP but with tail to fit Sloan®/Zurn® stop

**Model No: 81T231BTA-30**

### COMPLIES WITH:

- IAPMO listed to CSA B125.3/ASSE 1037
- ADA Compliant to meet Handicapped Accessibility Standard ICC/ ANSI A117.1 of less than 5 lbs operating force
- U.S. Patent # 6, 826, 455
- Other patents pending
- (Contact Delta Representative for State and/or Local Approvals)



### SPECIFICATION:

- Quiet action, Teck® exposed BATTERY operated diaphragm flush valve
- Right or left-hand supply installation
- Chloramine resistant diaphragm
- Forged brass diaphragm retainer
- Renewable seat
- Polished chrome plated finish
- Vacuum breaker
- RETROFIT KIT for Sloan®/Zurn® Manual or Electronic URINALS with 3/4" top inlet
- ADA compliant, automatic operation battery powered infrared sensor
- Polished chrome plated vandal resistant metal cover with top mounted sensor operated H2Optics® electronics
- Scratch resistant replaceable lens window
- Four (4) size AA alkaline batteries factory installed with valve in sleep mode for easy installation
- Hinged battery housing for easy maintenance
- Low battery flashing light (5000 flushes remaining) with battery strength indicator
- Optional 24 hour automatic flush factory set to OFF
- Set-up sensor range adjustment indicator lights
- 6 VDC input, 6 second arming delay
- Electronic operated non-hold-open metal manual override button with 5 second lockout
- Adjustable 114mm to 131mm (4.5" to 5.18") inlet/valve outlet centers
- Spud flange, spud nut, and 330mm (13") outlet tube.
- External water conserving adjustment: Factory Set to 1.9L(0.50 Gal.)  
Factory Set - FIELD ADJUSTABLE from 0.47 to 3.78 Litre Flush (1/8 to 1.0 GAL.)

### OPERATION:

- Not Available


***(Dimensional drawing on following page)***

Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced March 26, 2013.

Delta Faucet Company - 55 East 111th St. - Indianapolis, Indiana, USA 46280 - (317) 848-1812  
Delta Faucet Canada - 395 Matheson Blvd E - Mississauga, Ontario, Canada L4Z 2H2 - (905) 712-3030

Teck® flushometer valves are designed to operate at any supply pressure between 10 psi and 125 psi in accordance with CSA B125. The Teck® flush valve delivers the industry's highest peak flows to enhance bowl scrubbing. At high water pressures, splash out, noise or reduced life of plumbing components may be observed with a few models of water closet or urinal fixtures. To minimize or eliminate these effects, select a different model of water closet or urinal from the same or another manufacturer, or install a pressure reducing valve. If the installation does not allow for either of these options, the control stop adjusting screw may be used to reduce pressure to the valve.

\* NOTE: DIFFERENCE  
FROM STANDARD  
SLOAN/ZURN VALVE



Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced March 26, 2013.

Delta Faucet Company - 55 East 111th St. - Indianapolis, Indiana, USA 46280 - (317) 848-1812  
Delta Faucet Canada - 395 Matheson Blvd E - Mississauga, Ontario, Canada L4Z 2H2 - (905) 712-3030