



G4/G9 lamps offer bright and crisp white light in a very compact profile, while minimizing energy, maintenance costs and generating less heat compared to halogen equivalents. No UV or IR radiation in the light beam. Completely certified line voltage G9 lamps.

They are perfect for task lighting, under cabinet lighting display cases, pendant lighting, accent lighting throughout homes, museums, hotels, and restaurants.

JC (G4)



JD 2.5 W (G9)



JD 2.5 W (G9)



JD 3.5 W (G9)



| Order code                                        | Description                | Watts (W) | Base | Volts (VAC) | Colour temp. (K) | Average life <sup>1</sup> (hrs) | Initial lumens <sup>2</sup> (lm) | Beam angle (°) | Traditional equivalent (W) | Dimmable <sup>3</sup> (Yes/No) | Case qty |
|---------------------------------------------------|----------------------------|-----------|------|-------------|------------------|---------------------------------|----------------------------------|----------------|----------------------------|--------------------------------|----------|
| <b>JC*</b>                                        |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| MOL : 1 31/32 in. (41 mm) Dia. : 5/16 in. (16 mm) |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| 62805                                             | LED/G4/2.5W/30K/12V/ND/STD | 2.5       | G4   | 12          | 3 000            | 15 000                          | 200                              | 120            | 18                         | N                              | 100      |
| <b>JD*</b>                                        |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| MOL : 1 31/32 in. (50 mm) Dia. : 5/16 in. (16 mm) |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| 62804                                             | LED/G9/2.5W/30K/ND/STD     | 2.5       | G9   | 120         | 3 000            | 15 000                          | 200                              | 120            | 18                         | N                              | 100      |
| <b>JD**</b>                                       |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| MOL : 1 7/8 in. (48 mm) Dia. : 5/16 in. (16 mm)   |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| 63618                                             | LED/G9/2.5W/27K/STD        | 2.5       | G9   | 120         | 2 700            | 20 000                          | 190                              | 300            | 18                         | Y                              | 200      |
| 63619                                             | LED/G9/2.5W/30K/STD        | 2.5       | G9   | 120         | 3 000            | 20 000                          | 200                              | 300            | 18                         | Y                              | 200      |
| 63620                                             | LED/G9/2.5W/40K/STD        | 2.5       | G9   | 120         | 4 000            | 20 000                          | 210                              | 300            | 18                         | Y                              | 200      |
| <b>JD**</b>                                       |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| MOL : 1 7/8 in. (48 mm) Dia. : 25/32 in. (18 mm)  |                            |           |      |             |                  |                                 |                                  |                |                            |                                |          |
| 63444                                             | LED/G9/3.5W/27K/STD        | 3.5       | G9   | 120         | 2 700            | 30 000                          | 210                              | 300            | 18                         | Y                              | 500      |
| 63445                                             | LED/G9/3.5W/30K/STD        | 3.5       | G9   | 120         | 3 000            | 30 000                          | 225                              | 300            | 18                         | Y                              | 500      |
| 63446                                             | LED/G9/3.5W/40K/STD        | 3.5       | G9   | 120         | 4 000            | 30 000                          | 245                              | 300            | 18                         | Y                              | 500      |



DRY



DAMP



NO MERCURY



COMPLIANT



2 YEARS WARRANTY



UL US



ETL US



FC

# Decorative