
Technical Information Bulletin



Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	


ORDERING INFORMATION

Order code:	64475
Description:	LED/PLH/9W/35K/4P/ND/STD
UPC:	69549644755
Case quantity:	50
DLC unique ID:	PLC37IM9MBER



PERFORMANCE DATA

Shape:	PL Horizontal	
Base:	G24q - 4PIN	
Watts (W):	13	
Starting method:	Instant & Rapid Start	
Lamp voltage (VAC):	120 V-277 V / 347 V	
Color temperature (K)**:	3 500	
Life L70 (hrs):	50 000	
Initial Lumens (Im)*:	1 118	
Initial lumens per watt (Im/W):	86	
CRI:	80	
Beam angle (°):	120	
Swivel rotation (°):	170	
Operating temperature range:	-20°C / -4°F to 45°C / 113°F	





*Initial lumens range: +/- 10 % **Typical colour tempe

**Typical colour temperature range: +/- 5 %



ADDITIONAL INFORMATION

Turn power off before inspection, installation, or removal.

Risk of electrical shock - do not use where directly exposed to water or weather.

Not for use in totally enclosed luminaires.

Do not open - no user serviceable parts inside.

This device is not intended for use with emergency exit fixtures or emergency exit lights.

Not for use with dimmers.

This lamp only operates on electronic ballasts. If the lamp does not light up when the luminaire is energized, remove the lamp from the luminaire and contact the lamp manufacturer or a qualified electrician.

Qty	Description	Price
I accept the specifications o	f the luminaire configuration mentioned above.	
Name:		
Company:		
Signature:		Date:
Data is based upon tests performed in a contro	lled environment and representative of relative performance.	

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice