

Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____

ORDERING INFORMATION

Order code: 64000
 Description: LED/GU10/6.5W/30K/38/STD
 UPC: 69549640009
 Case quantity: 24

PERFORMANCE DATA

Shape: MR16
 Base: GU10
 Wattage (W): 6.5
 Lamp voltage (VAC): 120
 Colour temperature (K)**: 3 000
 Average life (L70 hours): 40 000
 Initial lumens (lm)*: 582
 Initial lumens per watt (lm/W): 90
 CRI: 82
 R9: 8
 Beam angle: 38
 CBCP: 1 242
 Power factor: 0.88
 Operating temperature range: - 40 °C / - 40 °F to 40 °C / 104 °F


*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 10 %



CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock – do not use where directly exposed to water or weather.
- Not for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.
- Not recommended for use with timers.
- Operating temperature: -40 °C / -40 °F to 40 °C / 104 °F
- 3 Years Limited Warranty.



MOL : 2 5/32 in. (55 mm)

Dia. : 1 35/32 in. (50 mm)

COMPATIBLE DIMMER LIST

Legrand	HCL453P
Cooper	DAL06P, SAL06P, SLC03P, AAL06
Leviton	IPL06, 6674, DSM10-1LZ
Lutron	CTCL-153P

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

March 14, 2016

STANDARD®