

Benefits

- Operates on programmed start electronic ballast only
- High system efficiency
- Low mercury content and TCLP compliant
- Energy savings and reduced maintenance cost
- High colour consistency
- One System extended lamp / ballast warranty



System comparison

Switching from a 54 watt T5HO lamp to a 49 watt T5HO lamp allows you to instantly save 5 watt per lamp without sacrificing any lighting performance.



T5HO



Dia. = 5/8 in. (16 mm)

T5HO - Program start

* Based on a 3 hour start ** Based on a 12 hour start

Order code	Description	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)		Efficacy (lm/W)	Case qty
24 watts											
10237	F24T5/41K/8/HO/PS/G5/STD	Min Bipin	4 100	85	25 000* 35 000**	2 000	1 900	22	559	83	25
10238	F24T5/30K/8/HO/PS/G5/STD	Min Bipin	3 000	85	25 000* 35 000**	2 000	1 900	22	559	83	25
10239	F24T5/35K/8/HO/PS/G5/STD	Min Bipin	3 500	85	25 000* 35 000**	2 000	1 900	22	559	83	25
39 watts											
10240	F39T5/30K/8/HO/PS/G5/STD	Min Bipin	3 000	85	25 000* 35 000**	3 500	3 325	34	864	90	25
10241	F39T5/35K/8/HO/PS/G5/STD	Min Bipin	3 500	85	25 000* 35 000**	3 500	3 325	34	864	90	25
10242	F39T5/41K/8/HO/PS/G5/STD	Min Bipin	4 100	85	25 000* 35 000**	3 500	3 325	34	864	90	25
49 watts											
60016	F49T5/30K/8/HO/PS/G5/STD ESV	Min Bipin	3 000	85	25 000* 35 000**	5 000	4 750	46	1 168	102	25
60017	F49T5/35K/8/HO/PS/G5/STD ESV	Min Bipin	3 500	85	25 000* 35 000**	5 000	4 750	46	1 168	102	25
60018	F49T5/41K/8/HO/PS/G5/STD ESV	Min Bipin	4 100	85	25 000* 35 000**	5 000	4 750	46	1 168	102	25
60019	F49T5/50K/8/HO/PS/G5/STD ESV	Min Bipin	5 000	85	25 000* 35 000**	5 000	4 750	46	1 168	102	25
54 watts											
10243	F54T5/30K/8/HO/PS/G5/STD	Min Bipin	3 000	85	25 000* 35 000**	5 000	4 750	46	1 168	93	25
10244	F54T5/35K/8/HO/PS/G5/STD	Min Bipin	3 500	85	25 000* 35 000**	5 000	4 750	46	1 168	93	25
10245	F54T5/41K/8/HO/PS/G5/STD	Min Bipin	4 100	85	25 000* 35 000**	5 000	4 750	46	1 168	93	25
10613	F54T5/FS/HO/PS/G5/STD	Min Bipin	5 700	92	25 000* 35 000**	5 000	4 750	46	1 168	93	25
58149	F54T5/50K/8/HO/PS/G5/STD	Min Bipin	5 000	85	25 000* 35 000**	5 000	4 750	46	1 168	93	25
59897	F54T5/41K/8/HO/PS/G5/STD BULK	Min Bipin	4 100	85	25 000* 35 000**	5 000	4 750	46	1 168	93	25
80 watts											
10246	F80T5/30K/8/HO/PS/G5/STD	Min Bipin	3 000	85	25 000* 35 000**	7 000	6 650	58	1 473	88	25
10247	F80T5/35K/8/HO/PS/G5/STD	Min Bipin	3 500	85	25 000* 35 000**	7 000	6 650	58	1 473	88	25
10248	F80T5/41K/8/HO/PS/G5/STD	Min Bipin	4 100	85	25 000* 35 000**	7 000	6 650	58	1 473	88	25