

Benefits

- Excellent colour rendering
- Low mercury content and TCLP compliant
- Energy savings and reduced maintenance cost
- One System extended lamp / ballast warranty



Dia. = 1 3/16 in. (30 mm)



Dia. = 1 in. (26 mm)

U Bent - 800 series - Rapid Start

Order code	Description	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)	Efficacy (lm/W)	Case qty
28 watts										
57522	FB28T8/30K/8/U6/RS/G13/STD	Med Bipin	3 000	85	20 000	2 450	2 330	22 17/32 572	88	20
57519	FB28T8/35K/8/U6/RS/G13/STD	Med Bipin	3 500	85	20 000	2 450	2 330	22 17/32 572	88	20
57518	FB28T8/41K/8/U6/RS/G13/STD	Med Bipin	4 100	85	20 000	2 450	2 330	22 17/32 572	88	20
31 watts										
58697	FB31T8/41K/8/U1/RS/G13/STD	Med Bipin	4 100	82	20 000	2 750	2 600	22 17/32 572	89	20
31 watts										
58698	FB31T8/35K/8/U1/RS/G13/STD	Med Bipin	3 500	82	20 000	2 750	2 600	22 17/32 572	89	20
32 watts Earthsaver										
10482	FB32T8/30K/8/U6/RS/G13/STD ESV	Med Bipin	3 000	85	20 000	2 550	2 220	22 17/32 572	80	20
10483	FB32T8/35K/8/U6/RS/G13/STD ESV	Med Bipin	3 500	85	20 000	2 550	2 220	22 17/32 572	80	20
10484	FB32T8/41K/8/U6/RS/G13/STD ESV	Med Bipin	4 100	85	20 000	2 550	2 220	22 17/32 572	80	20
10406	FB32T8/50K/8/U6/RS/G13/STD ESV	Med Bipin	5 000	86	20 000	2 550	2 220	22 17/32 572	80	20

Circline - Rapid Start

Order code	Description	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length (in.) (mm)	Efficacy (lm/W)	Case qty
20 watts										
58984	FC6T9/CW/RS/4P/STD	G10q-4	4 100	82	10 000	890	710	6 1/2 165	45	24
22 watts										
58985	FC8T9/WW/RS/4P/STD	G10q-4	3 000	82	10 000	1 450	1 910	8 9/32 210	45	24
58983	FC8T9/CW/RS/4P/STD	G10q-4	4 100	82	10 000	1 350	1 110	8 9/32 210	45	24
58982	FC8T9/DL/RS/4P/STD	G10q-4	6 500	82	10 000	1 210	995	8 9/32 210	45	24
32 watts										
58986	FC12T9/CW/RS/4P/STD	G10q-4	4 100	82	10 000	2 300	1 880	12 305	72	24
58987	FC12T9/DL/RS/4P/STD	G10q-4	6 500	82	10 000	2 000	1 640	12 305	63	24
40 watts										
58988	FC16T9/CW/RS/4P/STD	G10q-4	4 100	82	10 000	3 150	2 585	16 406	79	24