



S11904

4W/LED/T5/830/BP

4W T5 LED; Miniature bi-pin base; 3000K; 50000 Average rated hours; 400 Lumens; 120-277V; Type B; Ballast Bypass; Double Ended Wiring



Features

- No ballast or external driver required
- Available in 6", 9", 12", & 21"
- Direct wire 120-277V line voltage
- Double ended wiring
- NSF Approved
- PET Shatterproof coated
- 5 year Limited warranty

S11904

Replaces F8T5/WW lamps

| Item Number | UPC | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Power Factor | Lamp Shape |
|-------------|--------------|---------|-------|---------------------|------------------------|--------------|------------|
| S11904 | 045923119040 | 120-277 | 4 | 50/60Hz | 8W | 0.90 | T5 |

| Base | ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens |
|------------------|-----------|------------------|-----------------------|---------|---------------|---------------|----------------|
| Miniature Bi-Pin | G5 | 4W/LED/T5/830/BP | Non-Dimmable | Frosted | 11-29/32" | 0-5/8" | 400 |

| Average Rated Hours | Kelvin Temp | Color | CRI | Beam Spread Deg | Operating Temperature | Pack | CEC Status |
|---------------------|-------------|------------|-----|-----------------|--|------|-------------------------------|
| 50000 | 3000 | Warm White | 80 | 240 | -25C (-13F) to a maximum of +45C (+113F) | 10 | Lawful for sale in California |

| Material | RoHS Compliant | UL or ETL Listed | UL Classification | Warranty |
|----------|----------------|------------------|--|--------------------------------|
| Glass | Yes | Yes | cULus Classified - Damp Location Rated | 5 Year Limited |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051