## SATCO' NUVO

Project Name

Location

Prepared By



## SATCO S11920

13.5T8/LED/48-830/DIM-BP

Notes

General	
Status	Active
Watts	13.5
Volts	120V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	1700
Beam Spread	220
Dimmable	Yes - Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120 line voltage; No ballast or exter driver required
Power Factor	
Fower Factor	0.9
Operating Temperature	
	-20C (-4F) to a maximum of +45
Operating Temperature	-20C (-4F) to a maximum of +45
Operating Temperature Physical	-20C (-4F) to a maximum of +45 (+113F)
Operating Temperature Physical MOL	-20C (-4F) to a maximum of +45 (+113F) 48
Operating Temperature Physical MOL MOD	-20C (-4F) to a maximum of +45 (+113F) 48 1
Operating Temperature Physical MOL MOD Lens Finish	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted
Operating Temperature Physical MOL MOD Lens Finish Lens Material	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Additional Information Additional Info	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Additional Information	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Additional Information Additional Info	-20C (-4F) to a maximum of +45     (+113F)      48     1     Frosted     Glass     White      All glass tube     Approved for use with tube gua     Install only in non-shunted     lampholders
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube Approved for use with tube gua Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs
Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color  Additional Information  Additional Info Tube Guard Use Installation Notes  Warranty  Compliance	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube Approved for use with tube gua Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs
Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color  Additional Information Additional Info Tube Guard Use Installation Notes Warranty	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube Approved for use with tube gua Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs Ballast Bypass
Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color  Additional Information Additional Info Tube Guard Use Installation Notes Warranty  Compliance Safety Listing	<ul> <li>-20C (-4F) to a maximum of +45 (+113F)</li> <li>48</li> <li>1</li> <li>Frosted</li> <li>Glass</li> <li>White</li> <li>All glass tube</li> <li>Approved for use with tube gua</li> <li>Install only in non-shunted lampholders</li> <li>5 Year Limited - T8 LED Bulbs Ballast Bypass</li> <li>cULus Classified</li> </ul>
Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color  Additional Information  Additional Info Tube Guard Use Installation Notes  Warranty  Compliance Safety Listing Location Rating	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube Approved for use with tube gua Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs Ballast Bypass CULus Classified Damp
Operating Temperature         Physical         MOL         MOD         Lens Finish         Lens Material         Housing Color         Additional Information         Additional Info         Tube Guard Use         Installation Notes         Warranty         Compliance         Safety Listing         Location Rating         Energy Star	-20C (-4F) to a maximum of +48 (+113F)         48         1         Frosted         Glass         White         All glass tube         Approved for use with tube gua         Install only in non-shunted         lampholders         5 Year Limited - T8 LED Bulbs         Ballast Bypass         cULus Classified         Damp         No
Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color  Additional Information  Additional Info Tube Guard Use Installation Notes  Warranty  Compliance Safety Listing Location Rating Energy Star DLC Approved	<ul> <li>20C (-4F) to a maximum of +45 (+113F)</li> <li>48</li> <li>1</li> <li>Frosted</li> <li>Glass</li> <li>White</li> <li>All glass tube</li> <li>Approved for use with tube gua</li> <li>Install only in non-shunted lampholders</li> <li>5 Year Limited - T8 LED Bulbs Ballast Bypass</li> <li>cULus Classified</li> <li>Damp</li> <li>No</li> <li>Yes</li> </ul>
Operating Temperature         Physical         MOL         MOD         Lens Finish         Lens Material         Housing Color         Additional Information         Additional Info         Tube Guard Use         Installation Notes         Warranty         Compliance         Safety Listing         Location Rating         Energy Star         DLC Approved         DLC ID	-20C (-4F) to a maximum of +45 (+113F) 48 1 Frosted Glass White All glass tube Approved for use with tube gua Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs Ballast Bypass CULus Classified Damp No Yes PLV12B1YBIYP

in f 7 0

Copyright 2020 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>https://www.satco.com/</u>

FCC Compliant	

NSF Approved

Yes - Approved

Yes

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>https://www.satco.com/</u>

