

## S29395

80W/LED/HID/5000K/100-277V/EX39 80 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
  Damp location IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection 5KV
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
17.3 inch	9.25 inch	9.25 inch				

Optional accessory: In-line surge protector 80-929



S29395

Item	Product	UPC	Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	UPC	Voltage		Frequency	Equivalent	Equivalent

S29395	Hi-Pro (	045923293955		100 - 277	80	5	0/60Hz	400W		1	100W	
HID Equivalent	Base	ANSI Base		Lamp C	Code			ole/Non- nable	Finish	MOL In Inches	MOD In Inches	
320W	Mogul Extended	EX39	39 80W/LED/HID/5000K/10 277V/EX39			00-	Non-Di	Non-Dimmable White		9-1/4"	5.87"	
Initial Lumer	Average Ra NS Hours	ted	Kelvin Temp	Color	CR	Bea	am Spread Deg	Ope	erating Tem	perature	Pack	
10640	50000		5000	Natural Li	ght 80+	-	300	-20C (	-4F) to a m +65C (+14		12	
Package Type	CEC Status		DLC ID:		RoHS Compliar	nt	UL Classific	ation	Warranty		ermal Igement	
Box	Lawful for sale California		PE5MD5J <u>Search</u>	Q	Yes		cULus - W Location Ra		<u>5 Year</u> Limited	More De	tails About	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051