



# S39977

15T8/LED/48-840/DR  
 15W T8 LED; Medium bi-pin base; 4000K; 50000 Average  
 rated hours; 2200 Lumens; Type A; Ballast dependent

### Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube



S39977

\*May not be compatible with every ballast. Refer to the ballast compatibility chart.

Ballast required.

View:

- [Ballast Compatibility Chart](#)
- [Dimmable Ballast Compatibility Chart](#)
- [Emergency Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code	
S39977	045923399770	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-840/DR	
Dimmable/Non-Dimmable	Suggested Dimmers		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
Dimmable* Ballast Dependent	Check Ballast MFG for Dimmer Compatibility		Gloss White	48"	1.00"	2200	50000	4000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	
Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PL3A7LM1DMBQ	
RoHS Compliant			UL or ETL Listed	UL Classification		Warranty		



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

