

S9030

5.5A15/LED/2700K/120V

5.5 watt; A15 LED; Frosted; 2700K; Medium base; 230 Degree beam spread; 120 voltsm spread; 120 volts

Features

- Solid State LED lighting
- A shaped replacement lamp
- Long life
- Dimmable
- Approved for enclosed fixtures

Operating temperature: -20°C (-4°F) to a maximum of +45°C (113°F); Not for use in ovens



S9030

Item Number		UPC		Voltage	Watts	Incandescent Equivalent		Power Factor La		Lamp Sh	nape	Base	
S9030		045923090301		120	5.5	40W	40W		0.79			Medium	
ANSI Base	Lamp Code		Dimmable/Non- Dimmable		Suggeste Dimmers	Finish		MOL In MOD Inches Inche			Initial Lumens		
E26	5.5A1	5A15/LED/2700K/120V		Dimmable		Compatible dimmers for S	— ⊢r	osted	3-15/16	6" 1-7	7/8''	450	
Average Rated Hours		Kelvin Temp	Color	CRI	Beam Spre Deg	ad Ope	Operating Temperature			Pac	k Pa	ackage Type	
25000		2700	Warm White	80	230	`	-20C (-4F) to a maxii (+113F); Not for u			24/6	6	Box	
ENERGY STAR		RoHS Compliant		Fixture Type		UL or ETL Listed	III Classification				Warranty		
ENERGY STAR		R Yes		Enclosed Rated		Yes	cULus -	Location	Rated	3 Year Limited			



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051