



LED General Purpose

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.

From Omni lamps to small halogen replacements, these lamps deliver a brighter look and provide the same even, crisp and comfortable lighting as traditional lamps. A wide selection of colour temperatures is offered to obtain the desired lighting effect and can be adapted to all applications.



| Order code | Description | Watts (W) | Base | Volts (VAC) | Colour temp. (K) | Finish | CRI | Life L70 (hrs) | Lumen output (lm) | Traditional equivalent (W) | Dimming capability (Yes/No) | Case qty (inner/master) |
|---------------------------------|-----------------------------|--------------|------|-------------|------------------|--------|-----|----------------|---------------------|----------------------------|-----------------------------|-------------------------|
| A19 | | | | | | | | | | | | |
| 40 W equivalent | | | | | | | | | | | | |
| 64809 | LED/OMNI/S3/5.5W/27K/STD | 5.5 | E26 | 120 | 2 700 | Frost | 81 | 25 000 | 455 | 40 | Yes | 1/60 |
| 66177 | LED/A19/S4/6W/30K/STD | 6 | E26 | 120 | 3 000 | Frost | 84 | 25 000 | 533 | 40 | Yes | 6/48 |
| 66178 | LED/A19/S4/6W/40K/STD | 6 | E26 | 120 | 4 000 | Frost | 86 | 25 000 | 535 | 40 | Yes | 1/60 |
| 64812 | LED/OMNI/S3/5.5W/50K/STD | 5.5 | E26 | 120 | 5 000 | Frost | 86 | 25 000 | 545 | 40 | Yes | 1/60 |
| 60 W equivalent | | | | | | | | | | | | |
| 66180 | LED/A19/S4/9.8W/27K/STD | 9.8 | E26 | 120 | 2 700 | Frost | 83 | 25 000 | 814 | 60 | Yes | 6/48 |
| 66181 | LED/A19/S4/9.8W/30K/STD | 9.8 | E26 | 120 | 3 000 | Frost | 83 | 25 000 | 848 | 60 | Yes | 6/48 |
| 66182 | LED/A19/S4/9.8W/40K/STD | 9.8 | E26 | 120 | 4 000 | Frost | 86 | 25 000 | 874 | 60 | Yes | 6/48 |
| 66183 | LED/A19/S4/9.8W/50K/STD | 9.8 | E26 | 120 | 5 000 | Frost | 85 | 25 000 | 858 | 60 | Yes | 6/48 |
| 60 W equivalent - 4 pack | | | | | | | | | | | | |
| 66970 | LED/A19/9.8W/27K/STD 4P | 9.8 | E26 | 120 | 2 700 | Frost | 83 | 25 000 | 814 | 60 | Yes | 6/48 |
| 66971 | LED/A19/9.8W/30K/STD 4P | 9.8 | E26 | 120 | 3 000 | Frost | 83 | 25 000 | 848 | 60 | Yes | 6/48 |
| 66972 | LED/A19/9.8W/40K/STD 4P | 9.8 | E26 | 120 | 4 000 | Frost | 86 | 25 000 | 874 | 60 | Yes | 6/48 |
| 66973 | LED/A19/9.8W/50K/STD 4P | 9.8 | E26 | 120 | 5 000 | Frost | 85 | 25 000 | 858 | 60 | Yes | 6/48 |
| 60 W equivalent - GU24 | | | | | | | | | | | | |
| 66275 | A19/9.8W/27K/GU24/PRO/STD | 9.8 | GU24 | 120 | 2 700 | Frost | 83 | 25 000 | 814 | 60 | Yes | 6/48 |
| 66276 | A19/9.8W/30K/GU24/PRO/STD | 9.8 | GU24 | 120 | 3 000 | Frost | 82 | 25 000 | 887 | 60 | Yes | 6/48 |
| 66277 | A19/9.8W/40K/GU24/PRO/STD | 9.8 | GU24 | 120 | 4 000 | Frost | 86 | 25 000 | 868 | 60 | Yes | 6/48 |
| 75 W equivalent | | | | | | | | | | | | |
| 66184 | LED/A19/S4/11W/27K/STD | 11 | E26 | 120 | 2 700 | Frost | 81 | 25 000 | 1 109 | 75 | Yes | 1/60 |
| 66185 | LED/A19/S4/11W/30K/STD | 11 | E26 | 120 | 3 000 | Frost | 83 | 25 000 | 1 172 | 75 | Yes | 1/60 |
| 66186 | LED/A19/S4/11W/40K/STD | 11 | E26 | 120 | 4 000 | Frost | 85 | 25 000 | 1 196 | 75 | Yes | 6/48 |
| 66187 | LED/A19/S4/11W/50K/STD | 11 | E26 | 120 | 5 000 | Frost | 86 | 25 000 | 1 178 | 75 | Yes | 6/48 |
| 100 W equivalent | | | | | | | | | | | | |
| 65415 | LED/A21/S3/16W/27K/STD | 16 | E26 | 120 | 2 700 | Frost | 83 | 15 000 | 1 600 | 100 | Yes | 1/60 |
| 66189 | LED/A19/S4/15W/30K/STD | 15 | E26 | 120 | 3 000 | Frost | 81 | 25 000 | 1 630 | 100 | Yes | 6/48 |
| 66190 | LED/A19/S4/15W/40K/STD | 15 | E26 | 120 | 4 000 | Frost | 85 | 25 000 | 1 692 | 100 | Yes | 6/48 |
| 66191 | LED/A19/S4/15W/50K/STD | 15 | E26 | 120 | 5 000 | Frost | 85 | 25 000 | 1 725 | 100 | Yes | 6/48 |
| Trilight | | | | | | | | | | | | |
| 65613 | LED/A19/S2/12W/27K/3WAY/STD | 3 9 12 | E26 | 120 | 2 700 | Frost | 81 | 25 000 | 280 950 1 200 | 30 70 100 | No | 6/24 |
| 65614 | LED/A19/S2/12W/30K/3WAY/STD | 3 9 12 | E26 | 120 | 3 000 | Frost | 83 | 25 000 | 280 950 1 200 | 30 70 100 | No | 6/24 |



DAMP

ENCLOSED
FIXTUREBEAM
SPREAD3
YEARS
WARRANTY

UL US



ENERGY STAR

Lumen values are derived from photometric testing.
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



A15



C12



G16.5



G25

| Order code | Description | Watts (W) | Base | Volts (VAC) | Colour temp. (K) | Finish | Life L70 (hrs) | Lumen output (lm) | Traditional equivalent (W) | Case qty (inner/master) |
|--------------|----------------------------|-----------|------|-------------|------------------|--------|----------------|-------------------|----------------------------|-------------------------|
| A15 | | | | | | | | | | |
| 66755 | A15/S2/5W/27K/CL/STD | 5 | E26 | 120 | 2 700 | Clear | 15 000 | 300 | 40 | 24/48 |
| 63744 | LED/A15/5W/27K/F/STD | 5 | E26 | 120 | 2 700 | Frost | 25 000 | 300 | 40 | 6/48 |
| 63731 | LED/A15/5W/40K/F/STD | 5 | E26 | 120 | 4 000 | Frost | 25 000 | 300 | 40 | 6/48 |
| 66758 | A15/S2/6W/27K/CL/STD | 6 | E26 | 120 | 2 700 | Clear | 15 000 | 514 | 60 | 24/48 |
| 63734 | LED/A15/7W/27K/F/STD | 7 | E26 | 120 | 2 700 | Frost | 25 000 | 507 | 60 | 6/48 |
| 66760 | A15/S2/6W/30K/CL/STD | 6 | E26 | 120 | 3 000 | Clear | 15 000 | 592 | 60 | 24/48 |
| 66761 | A15/S2/5.5W/30K/FR/STD | 5.5 | E26 | 120 | 3 000 | Frost | 15 000 | 511 | 60 | 24/48 |
| 63732 | LED/A15/7W/40K/F/STD | 7 | E26 | 120 | 4 000 | Frost | 25 000 | 505 | 60 | 6/48 |
| C12 | | | | | | | | | | |
| 63741 | LED/C12/3W/27K/E12/STD | 3 | E12 | 120 | 2 700 | Clear | 25 000 | 200 | 40 | 6/48 |
| 63739 | LED/C12/3W/27K/F/E12/STD | 3 | E12 | 120 | 2 700 | Frost | 25 000 | 200 | 40 | 6/48 |
| 63743 | LED/C12/5W/27K/STD | 5 | E26 | 120 | 2 700 | Clear | 25 000 | 316 | 60 | 6/48 |
| 66764 | C12/S2/4.5W/27K/E12/CL/STD | 4.5 | E12 | 120 | 2 700 | Clear | 15 000 | 322 | 60 | 24/48 |
| 66765 | C12/S2/4.5W/27K/E12/FR/STD | 4.5 | E12 | 120 | 2 700 | Frost | 15 000 | 331 | 60 | 24/48 |
| G16.5 | | | | | | | | | | |
| 63736 | LED/G16.5/3W/27K/E12/STD | 3 | E12 | 120 | 2 700 | Clear | 25 000 | 200 | 40 | 6/48 |
| 66766 | G16.5/S2/5W/27K/E12/CL/STD | 5 | E12 | 120 | 2 700 | Clear | 15 000 | 365 | 60 | 24/48 |
| 63738 | LED/G16.5/5W/27K/E12/F/STD | 5 | E12 | 120 | 2 700 | Frost | 25 000 | 375 | 60 | 6/48 |
| G25 | | | | | | | | | | |
| 66768 | G25/S2/7W/27K/FR/STD | 7 | E26 | 120 | 2 700 | Frost | 15 000 | 553 | 60 | 24/48 |
| 66769 | G25/S2/7W/30K/FR/STD | 7 | E26 | 120 | 3 000 | Frost | 15 000 | 553 | 60 | 24/48 |



Lumen values are derived from photometric testing. For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



02

| Order code | Description | Watts (W) | Base | Volts (VAC) | Colour temp. (K) | Finish | Life L70 (hrs) | Lumen output (lm) | Beam angle (°) | Traditional equivalent (W) | Dimming capability (Yes/No) | Case qty (inner/master) |
|--------------------|---------------------------|-----------|------|-------------|------------------|--------|----------------|-------------------|----------------|----------------------------|-----------------------------|-------------------------|
| G9 | | | | | | | | | | | | |
| 63618 | LED/G9/2.5W/27K/STD | 2.5 | G9 | 120 | 2 700 | Frost | 20 000 | 190 | 300 | 20 | Yes | 50/200 |
| 63619 | LED/G9/2.5W/30K/STD | 2.5 | G9 | 120 | 3 000 | Frost | 20 000 | 200 | 300 | 20 | Yes | 50/200 |
| 63620 | LED/G9/2.5W/40K/STD | 2.5 | G9 | 120 | 4 000 | Frost | 20 000 | 210 | 300 | 20 | Yes | 50/200 |
| 63444 ² | LED/G9/3.5W/27K/STD | 3.5 | G9 | 120 | 2 700 | Frost | 30 000 | 210 | 300 | 20 | Yes | 50/500 |
| 63445 ² | LED/G9/3.5W/30K/STD | 3.5 | G9 | 120 | 3 000 | Frost | 30 000 | 225 | 300 | 20 | Yes | 50/500 |
| 63446 ² | LED/G9/3.5W/40K/STD | 3.5 | G9 | 120 | 4 000 | Frost | 30 000 | 245 | 300 | 20 | Yes | 50/500 |
| 66692 | G9HO/S2/4W/27K/FR/STD | 4 | G9 | 120 | 2 700 | Frost | 10 000 | 430 | 330 | 40 | Yes | 50/200 |
| 66690 | G9HO/S2/4W/30K/CL/STD | 4 | G9 | 120 | 3 000 | Clear | 10 000 | 480 | 330 | 40 | Yes | 50/200 |
| 66693 | G9HO/S2/4W/30K/FR/STD | 4 | G9 | 120 | 3 000 | Frost | 10 000 | 450 | 330 | 40 | Yes | 50/200 |
| 66694 | G9HO/S2/4W/40K/FR/STD | 4 | G9 | 120 | 4 000 | Frost | 10 000 | 450 | 330 | 40 | Yes | 50/200 |
| 66691 | G9HO/S2/4W/50K/CL/STD | 4 | G9 | 120 | 5 000 | Clear | 10 000 | 480 | 330 | 40 | Yes | 50/200 |
| T3-R7S | | | | | | | | | | | | |
| 64466 ¹ | LED/R7S/5W/30K/78/ND/STD | 5 | R7S | 120 | 3 000 | Clear | 15 000 | 450 | 360 | 50 | No | 50/200 |
| 64467 ¹ | LED/R7S/8W/30K/118/ND/STD | 8 | R7S | 120 | 3 000 | Clear | 15 000 | 650 | 360 | 100 | No | 50/200 |

Lumen values are derived from photometric testing. For a complete list of compatible dimmers, please visit www.standardpro.com

