

S29934

12T8/LED/48-830/DR 12 watt T8 LED; Medium bi-pin base; 3000K; 50000 Average rated hours; 1700 lumens



Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

S29934

Warranty

Ballast required.

View:

Ballast Compatibility Chart

UL or ETL Listed

| Item Number U | | UPC | ; | Watts | Fluorescent Equivalent | | Lamp Shape | Base | | ANSI Base | Lamp Code | |
|-----------------------|------------------------|---|----------------|-----------|---------------------------|------------------|----------------|-------------------|----------------------------|--------------|--------------------|---------------|
| S25 | S29934 045923299346 | | 9346 | 12 | 25\ | W-32W | Т8 | Medium Bi- Pin | | G13 | 12T8/LED/48-830/DR | |
| Dimmable/Non-Dimmable | | | Finish |) | OL In ches | MOD In Inches | Initial Lumens | | Average Rated Hours | | Kelvin Temp | Color |
| Non-Dimmable | | | Gloss White | | 48'' | 1.00" | 1700 | | 50000 | | 3000 | Warm White |
| CRI | CRI Beam Operating Tem | | | nperature | Pack | Package Type | CEC Status | | DLC ID: | | RoHS Compliant | |
| 82 | 210 | -20C (-4F) to a maximum of +45C (+113F) | | | 10 | Box | | | PL6UOQKEXHCD DLC Search | | Yes | |

UL Classification



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051