

## **LED** High Intensity

Our high intensity LED lamps are an easy, cost saving retrofit solution that can replace up to 400 W HID lamps. With different color temperatures, wattages and base options, they are the perfect replacement for HID lamps. These LED retrofits are ideal for many applications such as churches, area lighting and industrial lighting.

No need for a time consuming fixture replacement, simply bypass the ballast and screw the lamp in. The ballast bypass is the best option for long term installations since it prevents the need to go back and replace the ballast at a later time, making it ideal for hard to reach spaces.



Durable heat sink design with silent integrated fan and safety cable included

Order code	·			Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (Im)	Bare lamp lumen (lm)	Operating position	Case qty (master)
High Bay	y Retrofit 100-277 V										
67048 <sup>1</sup>	CRNHB/150W/40K/BYP/100-277/ND/EX39/STD	150	EX39	100-277	4 000	80	50 000	17 195	21 000	Vertical	4
67049¹	CRNHB/150W/50K/BYP/100-277/ND/EX39/STD	150	EX39	100-277	5 000	80	50 000	17 929	21 000	Vertical	4

A safety cable is included with this lamp to secure its installation in the fixture
Make sure to use this cable when installing the lamp to prevent the lamp from falling down

*ST\_NDARD*°















LED chips mounted on top for a 360° light output





Ø 2 3/4" (70 mm)

22 W



36 W



54 W



120 W

Order code	Description	Watts	Base	Volts	Color temp.	CRI	Life L70	Lumen	Operating position	Case qty
				(VAC)	(K)		(hrs)	(lm)	poortion	(master)
360° 120-277 V										
67794 <sup>1</sup>	CRN/S2/22W/30K/BYP/120-277/ND/E26/STD	22	E26	120-277	3 000	80	50 000	2 579	Vertical	24
67795 <sup>1</sup>	CRN/S2/22W/40K/BYP/120-277/ND/E26/STD	22	E26	120-277	4 000	80	50 000	2 812	Vertical	24
67796	CRN/S2/22W/50K/BYP/120-277/ND/E26/STD	22	E26	120-277	5 000	80	50 000	2 668	Vertical	24
360° 12	0-347 V									
67923	CRN/S3/36W/30K/BYP/120-347/ND/E26/STD	36	E26	120-347	3 000	80	50 000	5 200	Vertical	12
67924	CRN/S3/36W/40K/BYP/120-347/ND/E26/STD	36	E26	120-347	4 000	80	50 000	5 200	Vertical	12
67925	CRN/S3/36W/50K/BYP/120-347/ND/E26/STD	36	E26	120-347	5 000	80	50 000	5 200	Vertical	12
67926	CRN/S3/54W/40K/BYP/120-347/ND/E39/STD	54	E39	120-347	4 000	80	50 000	7 800	Vertical	12
67927	CRN/S3/54W/50K/BYP/120-347/ND/E39/STD	54	E39	120-347	5 000	80	50 000	7 800	Vertical	12
67930	CRN/S3/120W/40K/BYP/120-347/ND/E39/STD	120	E39	120-347	4 000	80	50 000	16 800	Vertical	6
67931	CRN/S3/120W/50K/BYP/120-347/ND/E39/STD	120	E39	120-347	5 000	80	50 000	16 800	Vertical	6















Lumen values are derived from photometric testing


For a complete list of compatible ballasts and DLC qualified products, please visit www.standardpro.com

Not DLC

A safety cable is included with this lamp to secure its installation in the fixture


Make sure to use this cable when installing the lamp to prevent the lamp from falling down








40 W - E39




60 W

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (Im)	Bare lamp lumen (Im)	Operating position	Case qty (master)
180° 100	)-277 V										
6705212	CRN180/40W/40K/BYP/100-277V/ND/E26/STD	40	E26	100-277	4 000	80	50 000	3 706	6 000	Horizontal	12
67053 <sup>2</sup>	CRN180/40W/40K/BYP/100-277V/ND/E39/STD	40	E39	100-277	4 000	80	50 000	3 706	6 000	Horizontal	12
67054 <sup>2</sup>	CRN180/60W/40K/BYP/100-277V/ND/E39/STD	60	E39	100-277	4 000	80	50 000	5 658	9 000	Horizontal	12



Face down installation



Face out installation

## Traditional Equivalent

LED	CFL	Incandescent	HID
22 W	32 W - 40 W	150 W - 200 W	50 W - 75 W
36 W - 40 W	55 W - 65 W	300 W	100 W - 150 W
54 W - 60 W	85 W - 105 W	500 W	150 W - 200 W
100 W	-	-	200 W - 250 W
120 W	-	-	250 W
150 W	-	-	400 W

Lumen values are derived from photometric testing
For a complete list of compatible ballasts and DLC qualified
products, please visit www.standardpro.com

1 Not DLC

7 Two lamp support accessories are included with this lamp to
reduce weight on the socket and secure its installation in the fixture

## **Accessories**

Order code	Description
10985	Mogul to Medium socket adaptor
10587	Mogul to Mogul socket extension











