

Project: _____ Type: _____
 Drawn by: _____ Catalogue #: _____ Date: _____

Individual Spec Sheet

LED EDGELIT

LED CEILING LUMINAIRE

6"

ORDERING INFORMATION

Order code: 67365
Model number: LED/CL6/EDGELIT/11W/30K/FM/RND/BK/STD
UPC: 069549673656
Case quantity: 20

PHYSICAL DATA

Size in. (mm): 6 (156)
Shape: Round
Type: Ceiling
Trim finish: Black
Lens material: Frosted Polycarbonate
Mounting: Surface Mount/Flush-mount

PERFORMANCE DATA

Watts (W): 11
Volts (VAC): 120
Colour temperature (K): 3 000
Lumen output (lm): 809.5
Lumen per Watts (lm/W): 70
CRI: >80
Life L70 (h): 50 000
Beam angle (°): 120
THD (%): >15
Power factor: 0.95
Dimmer type: Forward-Reverse phase
Frequency (Hz): 60
Operating temp. range: -20 °C to 50 °C (-4 °F to 122 °F)

¹ Typical colour temperature range: +/- 5 %

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

COMPATIBLE DIMMERS

Brand	Model
COOPER	RRD-6NA-WH, AAL06, SLC03P
LEGRAND	PD-5NE, RH703PTUTC
LEVITON	6615, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1
LUTRON	DVCL-153P, AYCL-253P, SELV-300P

NOTE: The above table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation. Some dimmers may require more than one product for stable operation. The maximum number of products is determined by the dimmer wattage rating with LEDs. Be careful, these dimmers have different ratings depending on the product type. Again, refer to the dimmer installation instructions.

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



5 yrs
warranty

quick ship

LED fixture

dimmmable fixture


wet location



ICES
005




DIMENSIONS



PHOTOMETRIC DATA¹

67365 • LED/CL6/EDGELIT/11W/30K/FM/RND/BK/STD • 809.5 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	221.5	27.4
0-40	365.9	45.1
0-60	643.9	79.5
60-90	161.2	19.9
70-100	65.0	8
90-120	1.6	0.2
0-90	805.1	99.4
90-180	4.5	0.6
0-180	809.5	100

Illuminance at a distance

Center beam fc		Beam width	
17.0'	0.97	50.9'	51.1'
34.0'	0.24	101.8'	102.2'
51.0'	0.11	152.7'	153.3'
68.0'	0.06	203.6'	204.4'
85.0'	0.04	254.5'	255.6'
102.0'	0.03	305.4'	306.7'

Vert. spread: 112.5°
Horiz. spread: 112.7°

¹ Complete IES files available on our website.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____

Company: _____

Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.