Technical Information Bulletin





Date:	 Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

ORDERING INFORMATION

Order code: 68002

LED/A19/S2/9W/30K/STD 4P **Description:**

UPC: 069549680029

1 / 96 Case quantity:



A19 Shape: Wattage (W): Base: E26 Lamp voltage (VAC): 120 Colour temperature (K)**: 3 000 Life L70 (hrs): 25 000 Initial lumens (lm)*: 800 Initial lumens per watt (Im/W): 89 80 CRI: Beam angle (°): 220 Power factor: 0.70

- 30 °C / - 22 °F to 40 °C / 104 °F Operating temperature range:

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %



damp







enclosed











CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock do not use where directly exposed to water or weather.
- · Suitable for use in totally enclosed luminaires.
- · Suitable for use in damp locations.
- Do not open no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.



COMPATIBLE DIMMERS

Brand	Model	
Lutron	PD-5NE, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVRP-253P, SELV-300P, MACL-153P	
Cooper	RRD-6NA, AAL06	
Leviton	IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1	
Legrand	RH703PTUTC	

Dimming performance might be impacted when using the above dimmers with only one lamp Full performance achieved with at two or more lamps.

Qty	Description	Price
I accept the spe	ecifications of the luminaire configuration m	entioned above.
Name:		
Company:		
Signature:		Date:

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.