



# LED General Purpose

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.

From Omni lamps to small halogen replacements, these lamps deliver a brighter look and provide the same even, crisp and comfortable lighting as traditional lamps. A wide selection of colour temperatures is offered to obtain the desired lighting effect and can be adapted to all applications.



02

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>A19</b>												
<b>40 W equivalent</b>												
64809	LED/OMNI/S3/5.5W/27K/STD	5.5	E26	120	2 700	Frost	81	25 000	455	40	Yes	1/60
66177	LED/A19/S4/6W/30K/STD	6	E26	120	3 000	Frost	84	25 000	533	40	Yes	6/48
66178	LED/A19/S4/6W/40K/STD	6	E26	120	4 000	Frost	86	25 000	535	40	Yes	6/48
64812	LED/OMNI/S3/5.5W/50K/STD	5.5	E26	120	5 000	Frost	86	25 000	545	40	Yes	1/60
<b>60 W equivalent</b>												
66180	LED/A19/S4/9.8W/27K/STD	9.8	E26	120	2 700	Frost	83	25 000	814	60	Yes	6/48
66181	LED/A19/S4/9.8W/30K/STD	9.8	E26	120	3 000	Frost	83	25 000	848	60	Yes	6/48
66182	LED/A19/S4/9.8W/40K/STD	9.8	E26	120	4 000	Frost	86	25 000	874	60	Yes	6/48
66183	LED/A19/S4/9.8W/50K/STD	9.8	E26	120	5 000	Frost	85	25 000	858	60	Yes	6/48
<b>60 W equivalent - 4 pack</b>												
66970	LED/A19/9.8W/27K/STD 4P	9.8	E26	120	2 700	Frost	83	25 000	814	60	Yes	6/48
66971	LED/A19/9.8W/30K/STD 4P	9.8	E26	120	3 000	Frost	83	25 000	848	60	Yes	6/48
66972	LED/A19/9.8W/40K/STD 4P	9.8	E26	120	4 000	Frost	86	25 000	874	60	Yes	6/48
66973	LED/A19/9.8W/50K/STD 4P	9.8	E26	120	5 000	Frost	85	25 000	858	60	Yes	6/48
<b>60 W equivalent - GU24</b>												
66275	A19/9.8W/27K/GU24/PRO/STD	9.8	GU24	120	2 700	Frost	83	25 000	814	60	Yes	6/48
66276	A19/9.8W/30K/GU24/PRO/STD	9.8	GU24	120	3 000	Frost	82	25 000	887	60	Yes	6/48
66277	A19/9.8W/40K/GU24/PRO/STD	9.8	GU24	120	4 000	Frost	86	25 000	868	60	Yes	6/48
<b>75 W equivalent</b>												
66184	LED/A19/S4/11W/27K/STD	11	E26	120	2 700	Frost	81	25 000	1 109	75	Yes	6/48
66185	LED/A19/S4/11W/30K/STD	11	E26	120	3 000	Frost	83	25 000	1 172	75	Yes	6/48
66186	LED/A19/S4/11W/40K/STD	11	E26	120	4 000	Frost	85	25 000	1 196	75	Yes	6/48
66187	LED/A19/S4/11W/50K/STD	11	E26	120	5 000	Frost	86	25 000	1 178	75	Yes	6/48
<b>100 W equivalent</b>												
66188	LED/A19/S4/15W/27K/STD	15	E26	120	2 700	Frost	82	25 000	1 629	100	Yes	6/48
66189	LED/A19/S4/15W/30K/STD	15	E26	120	3 000	Frost	81	25 000	1 630	100	Yes	6/48
66190	LED/A19/S4/15W/40K/STD	15	E26	120	4 000	Frost	85	25 000	1 692	100	Yes	6/48
66191	LED/A19/S4/15W/50K/STD	15	E26	120	5 000	Frost	85	25 000	1 725	100	Yes	6/48
<b>Trilight</b>												
65613	LED/A19/S2/12W/27K/3WAY/STD	3 9 12	E26	120	2 700	Frost	81	25 000	280 950 1 200	30 70 100	No	6/24
65614	LED/A19/S2/12W/30K/3WAY/STD	3 9 12	E26	120	3 000	Frost	83	25 000	280 950 1 200	30 70 100	No	6/24



Lumen values are derived from photometric testing. For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)



A15



C12



G16.5



G25

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Case qty (inner/master)
<b>A15</b>										
66755	A15/S2/5W/27K/CL/STD	5	E26	120	2 700	Clear	15 000	300	40	24/48
66756	A15/S2/5W/27K/FR/STD	5	E26	120	2 700	Frost	15 000	300	40	24/48
63731	LED/A15/5W/40K/F/STD	5	E26	120	4 000	Frost	25 000	300	40	6/48
66758	A15/S2/6W/27K/CL/STD	6	E26	120	2 700	Clear	15 000	514	60	24/48
66759	A15/S2/5.5W/27K/FR/STD	5.5	E26	120	2 700	Frost	15 000	496	60	24/48
66760	A15/S2/6W/30K/CL/STD	6	E26	120	3 000	Clear	15 000	592	60	24/48
66761	A15/S2/5.5W/30K/FR/STD	5.5	E26	120	3 000	Frost	15 000	511	60	24/48
66762	A15/S2/5.5W/40K/FR/STD	5.5	E26	120	4 000	Frost	15 000	530	60	24/48
<b>C12</b>										
63741	LED/C12/3W/27K/E12/STD	3	E12	120	2 700	Clear	25 000	200	40	6/48
63739	LED/C12/3W/27K/F/E12/STD	3	E12	120	2 700	Frost	25 000	200	40	6/48
63743	LED/C12/5W/27K/STD	5	E26	120	2 700	Clear	25 000	316	60	6/48
66764	C12/S2/4.5W/27K/E12/CL/STD	4.5	E12	120	2 700	Clear	15 000	322	60	24/48
66765	C12/S2/4.5W/27K/E12/FR/STD	4.5	E12	120	2 700	Frost	15 000	331	60	24/48
<b>G16.5</b>										
63736	LED/G16.5/3W/27K/E12/STD	3	E12	120	2 700	Clear	25 000	200	40	6/48
66766	G16.5/S2/5W/27K/E12/CL/STD	5	E12	120	2 700	Clear	15 000	365	60	24/48
63738	LED/G16.5/5W/27K/E12/F/STD	5	E12	120	2 700	Frost	25 000	375	60	6/48
<b>G25</b>										
66768	G25/S2/7W/27K/FR/STD	7	E26	120	2 700	Frost	15 000	553	60	24/48
66769	G25/S2/7W/30K/FR/STD	7	E26	120	3 000	Frost	15 000	553	60	24/48



Lumen values are derived from photometric testing. For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>G9</b>												
63618	LED/G9/2.5W/27K/STD	2.5	G9	120	2 700	Frost	20 000	190	300	20	Yes	50/200
63619	LED/G9/2.5W/30K/STD	2.5	G9	120	3 000	Frost	20 000	200	300	20	Yes	50/200
63620	LED/G9/2.5W/40K/STD	2.5	G9	120	4 000	Frost	20 000	210	300	20	Yes	50/200
63444 <sup>2</sup>	LED/G9/3.5W/27K/STD	3.5	G9	120	2 700	Frost	30 000	210	300	20	Yes	50/500
63445 <sup>2</sup>	LED/G9/3.5W/30K/STD	3.5	G9	120	3 000	Frost	30 000	225	300	20	Yes	50/500
63446 <sup>2</sup>	LED/G9/3.5W/40K/STD	3.5	G9	120	4 000	Frost	30 000	245	300	20	Yes	50/500
66692	G9HO/S2/4W/27K/FR/STD	4	G9	120	2 700	Frost	10 000	430	330	40	Yes	50/200
66690	G9HO/S2/4W/30K/CL/STD	4	G9	120	3 000	Clear	10 000	480	330	40	Yes	50/200
66693	G9HO/S2/4W/30K/FR/STD	4	G9	120	3 000	Frost	10 000	450	330	40	Yes	50/200
66694	G9HO/S2/4W/40K/FR/STD	4	G9	120	4 000	Frost	10 000	450	330	40	Yes	50/200
66691	G9HO/S2/4W/50K/CL/STD	4	G9	120	5 000	Clear	10 000	480	330	40	Yes	50/200
<b>T3-R7S</b>												
64466 <sup>1</sup>	LED/R7S/5W/30K/78/ND/STD	5	R7S	120	3 000	Clear	15 000	450	360	50	No	50/200
64467 <sup>1</sup>	LED/R7S/8W/30K/118/ND/STD	8	R7S	120	3 000	Clear	15 000	650	360	100	No	50/200

02

Lumen values are derived from photometric testing. For a complete list of compatible dimmers, please visit [www.standardpro.com](http://www.standardpro.com)

