







U-SHAPED SMART WINDOW AC

Let the fresh air in!

This unique U-shaped AC makes opening and closing your windows possible even while installed. The patented inverter technology achieves more than 35% energy savings and more precise temperature control* compared to traditional AC units. It also helps blocks noise coming from the compressor outside, allowing ultra-quiet operation as low as 42dB. Includes a quick-snap support bracket** and can be installed in 3 simple steps.

UNIQUE U-SHAPED DESIGN allows open/close window usage



WINDOW AC WITH Wi-Fi®

Control at your fingertips

Convenience is the name of the game with our line of Energy Star window air conditioners with Wi-Fi°! The *Perfect Home* app lets you control your energy usage by setting your room temperature remotely, or use the geofencing feature to automatically adjust the air conditioner settings. You can also go hands-free by connecting to your smart speaker with Amazon Alexa and Google Assistant.

Wi-Fi[®] is a registered trademark of Wi-Fi Alliance[®]



WIRELESS SMART CONTROL

All Perfect Aire smart Wi-Fi® enabled window ACs run on the Perfect Home app, so you can control your AC with your smartphone. Or, control with voice commands by connecting your AC to your Google Assistant or Amazon Alexa smart home speaker. Either way, you can customize the settings to your comfort level with special features such as:

- Share a single device with up to 20 household accounts
- Set a 7 day/24 hour schedule to turn the unit on and off when you want.
- Sleep Curve lets you customize the temperature range by the hour for your best night's sleep.
- Geofencing adjusts the machine's settings depending on the location of your phone's GPS.

*Compared to Federal minimum requirement. **For single or double hung windows 23"-36"; Minimal height of 14".



| SPECIFICATIONS | 1PACU8000 | 1PACU10000 | 1PACU12000 | |
|-----------------------------------|--|-----------------------|-----------------------|--|
| UPC | 842149090876 | 842149090883 | 842149090890 | |
| Energy Star | - Complete C | Amery C | dianty);; | |
| Wi-Fi | ~ | ~ | V | |
| Cooling Capacity (BTU) | 8,000 | 10,000 | 12,000 | |
| Heating Capacity (BTU) | _ | _ | _ | |
| Coverage Area (Sq. Ft.) | 350 | 450 | 550 | |
| CEER | 15 | 15 | 15 | |
| Amps | 8.78 | 10.17 | 12.0 | |
| Watts | 720 | 890 | 1,140 | |
| Window Width (Min./Max.) (In.) | 23-36 | 23-36 | 23-36 | |
| Window Height (Min.) (In.) | 19.5 | 19.5 | 19.5 | |
| Fan Speeds (Cool/Fan/Heat) | 3/3 | 3/3 | 3/3 | |
| Unit Dimension (W×H×D) (In.) | 22 × 13.5 × 19.25 | 22 × 13.5 × 19.25 | 22 × 13.5 × 19.25 | |
| Packaging Dimension (W×H×D) (In.) | 24.25 × 15.25 × 21.25 | 24.25 × 15.25 × 21.25 | 24.25 × 15.25 × 21.25 | |
| Weight (Net/Gross) (Lb.) | 55.5/66 | 57/67 | 59/69.75 | |
| Container Qty (40' HQ) | 492 | 492 | 492 | |
| Refrigerant | R32 | R32 | R32 | |
| Cord Length (Ft.) | 6.5 | 6.5 | 6.5 | |
| Outlet Configuration | 15A-115V | 15A-115V | 15A – 115V | |









| SPECIFICATIONS | 1PAWFC8000 | 1PAWFC10000 | 1PAWFC12000 | 1PAWFC14500 |
|-----------------------------------|-------------------------|----------------------------|--------------------|----------------------------|
| UPC | 842149001094 | 842149001100 | 842149001117 | 842149001124 |
| Energy Star | क्रमार्ग्य । एउटा एक | 60-1971-2 20-20-20-20-2 | entitiz vanoran | Same Till 2 Vision view |
| Wi-Fi | ✓ | · | · | ~ |
| Cooling Capacity (BTU) | 8,000 | 10,000 | 12,000 | 14,500 |
| Heating Capacity (BTU) | - | _ | _ | _ |
| Coverage Area (Sq. Ft.) | 350 | 450 | 550 | 700 |
| CEER | 11.4 | 11.4 | 11.4 | 11.3 |
| Amps | 6.27 | 7.8 | 10.1 | 11.8 |
| Watts | 700 | 875 | 1,050 | 1,280 |
| Window Width (Min./Max.) (In.) | 23-36 | 23-36 | 23-36 | 23-36 |
| Window Height (Min.) (In.) | 14 | 15.5 | 15.5 | 15.5 |
| Fan Speeds (Cool/Fan/Heat) | 3/3 | 3/3 | 3/3 | 3/3 |
| Unit Dimension (W×H×D) (In.) | 16.25 × 13.5 × 18.5 | 19 × 14.75 × 22.75 | 19 × 14.75 × 22.75 | 19 × 14.75 × 21.5 |
| Packaging Dimension (W×H×D) (In.) | 18.5 × 14.75 × 22 | 22 × 17.25 × 24.25 | 22 × 17.25 × 24.25 | 22 × 17 × 23 |
| Weight (Net/Gross) (Lb.) | 456/53.5 | 58.75/65.5 | 65/72.5 | 71/78.5 |
| Container Qty (40' HQ) | 700 | 468 | 468 | 498 |
| Refrigerant | R32 | R32 | R32 | R32 |
| Cord Length (Ft.) | 6.5 | 6.5 | 6.5 | 6.5 |
| Outlet Configuration | 15A-115V | 15A - 115V | 15A-115V | 15A-115V |

10 | perfectaire.us | 11