

VINYL ELECTRICAL TAPE



HIGHLY CONFORMABLE

CSA/UL APPROVED

DESCRIPTION

Special vinyl film backing coated with a non-corrosive adhesive. Excellent conformability. CSA approved with a temperature range of -7°C to 80°C. Colours: 02 Red, 05 Yellow, 07 Green, 08 Blue, 10 White.

MAIN FEATURES

- PVC has excellent memory.
- Very conformable.
- Temperature range.
- Water resistant.
- CSA/UL approved for -7°C to 80°C (19°F to 175°F).

APPLICATIONS

- Splicing of appliances wires.
- Repairs in junction boxes.
- Insulation of wires.
- Used as a masking tape in electro plating.
- All electrical splicing.
- Wrapping battery cables.
- Protection against solvents and corrosion.

TECHNICAL DATA

Colour	Black[01], Red[02], Yellow[05], Green[07]
.....	Blue[08], White[10]
Backing	PVC film
Adhesive	Natural rubber
Thickness	7 mil
Dielectric Strength	7000 volts
Adhesion	18 lb/in
Tensile Strength	20 lb/in
Elongation	225%
Temperature Resistance	-7°C to 80°C (-19.4°F to 176°F)
Meets CSA Spec	LR 31971
Meets UL Spec	E - 50292

STOCK SIZE

18 mm x 20 m

Please note:

The technical characteristics quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities.