



KRYLON® INDUSTRIAL INTERIOR/EXTERIOR MAINTENANCE PAINTS

Foolproof Touch-Up... Anytime!



- The most asked-for spray paint in the industrial marketplace
- VOC-compliant, acrylic lacquer formula
- Maximum coverage with excellent adhesion
- Dries fast, in just 12 minutes to the touch
- Tough, high-gloss finish



CLEANERS, DEGREASERS
LUBES AND SEALANTS

SUPERIOR
LUBRICANTS

PAINTS, COATINGS
AND PRIMERS

CAULKS, SEALANTS
AND ADHESIVES

BRUSHES, ROLLER COVERS
AND ACCESSORIES

All other aerosol paints require the user to do retouching within one hour...or wait up to three days! If you ignore the "touch-up window," the paint can wrinkle, lift, and end up looking like an alligator. Krylon® Industrial Interior/Exterior Paint has the exclusive Touch-Up Anytime feature, so even inexperienced painters can get great results...every time...without the wait!

For Interior/Exterior Use On: Any metal or wood surface, including motors, tools, pipelines, conduit, ducts, drums, cabinets, furniture, and for color coding steel and lumber.

No Runs, No Drips, No Errors!™



PHYSICAL PROPERTIES

	INT/EXT (5-BALL)	PRIMER
PRODUCT TYPE:	Acrylic Lacquer	Alkyd
FINISH:	High Gloss	Flat
NET WEIGHT:	12 oz.	12 oz.
CASE PACK:	6	6
DRYING TIMES @ 70°F @ 50% R.H.:		
TO TOUCH:	12 minutes	12 minutes
TO HANDLE:	30 minutes	1 hour
MAX HARDNESS:	30 minutes	30 minutes (sandability)
COVERAGE:	15 – 20 sq. ft.	15 – 20 sq. ft.
RECOAT:	Anytime	Anytime
TEMP RESISTANCE:	<150°F	Up to 300°F
PRIMER:	Recommended	N/A
GAS & OIL RESISTANCE:	Film softens after 15 minutes	Stains
CLEAN-UP:		
WET:	Lacquer Thinner	Mineral Spirits
DRY:	Lacquer Thinner	Lacquer Thinner
SHELF LIFE:	3 years from date of manufacture	

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove visible rust on metal with a wire brush, sandpaper or scraper. Sand metal, wood or plastic with #220 grit sandpaper. Clean to remove grease, oil and dirt. Allow to dry thoroughly, then wipe with a tack cloth. Use a primer on new wood and on new or rusted metal to smooth uneven surfaces, or when dramatically changing color. For best results, use with Krylon Industrial White (K01315), Gray (K01318) or Ruddy Brown (K01317) Primers. Allow primer to dry for at least 30 minutes before lightly sanding and topcoating with Krylon Industrial Interior/Exterior paints.

Distributed By:

APPLICATION

Surface preparation must be completed as indicated. Remove cap by following instructions on the top. Test spray on an inconspicuous area for substrate compatibility. Spray 10" to 12" from surface in a sweeping motion. Apply several thin coats. Do not apply in one continuous spray. Release the spray button after each pass. When finished, clean valve by holding can upside down and spraying until only clear gas is released. If spray valve becomes clogged, pull spray button off and clean it in lacquer thinner. DO NOT stick pins or wire into can opening. Replace spray button with valve opening pointing away from body. Replace cap for future use.

PACKAGING

Part #	Color	UPC Code
ENAMELS		
K01301	Crystal Clear	075577000548
K01501	Gloss White	075577000555
K01502	Flat White	075577000562
K01506	Almond	075577000579
K01508	Semi-Gloss White	075577000586
K01601	Gloss Black	075577000593
K01602	Ultra Flat Black	075577000609
K01604	Shadow Gray	075577000814
K01605	Stone Gray	075577000821
K01606	Pewter Gray	075577000616
K01608	Smoke Gray	075577000623
K01613	Semi-Gloss Black	075577000630
K01806	Sun (Safety) Yellow	075577000647
K01901	Regal Blue	075577000654
K01910	True (Safety) Blue	075577000661
K01913	Purple (Safety)	075577000678
K02001	Hunter Green	075577000685
K02016	Emerald (Safety) Green	075577000692
K02101	Cherry Red	075577000708
K02108	Banner (Safety) Red	075577000715
K02501	Leather Brown	075577000722
K02504	Khaki (Beige)	075577000739
PRIMERS		
K01314	Platinum Primer	075577000746
K01315	White Primer	075577000760
K01316	Black Primer	075577000777
K01317	Ruddy Brown Primer	075577000784
K01318	Gray Primer	075577000791

CARTON DIMENSIONS:

L 8.44" x W 5.75" x H 8.44"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

www.paintdocs.com

WEB: www.KPG-Industrial.com

CUSTOMER SERVICE: 1-800-777-2966

TECHNICAL INFORMATION: 1-800-251-2486

COLOR SELECTION GUIDE

ENAMELS

K01301	K01501
K01502	K01506
K01508	K01601
K01602	K01604
K01605	K01606
K01608	K01613
K01806	K01901
K01910	K01913
K02001	K02016
K02101	K02108
K02501	K02504
PRIMERS	
K01314	K01315
K01316	K01317
K01318	



Krylon Products Group
101 Prospect Ave. NW
Cleveland, OH 44115
www.KPG-Industrial.com
Tel: 1-800-777-2966