



# TECHNICAL DATA SHEET

**LePAGE®**  
**NO MORE NAILS®**  
Mounting Tape

**Henkel Canada Corporation**  
Professional and Consumer Adhesives  
Mississauga, ON L5T 3A5  
Phone 1-800-624-7767  
Fax (440) 937-7067  
[www.henkel.com](http://www.henkel.com) [www.lepageproducts.com](http://www.lepageproducts.com)



Item #	Package	Size
778548	Carded Roll	1.5 m

## DESCRIPTION

LePage® No More Nails® Mounting Tape is a super strong, double-sided tape for fast, clean and durable mounting indoors and outdoors. One roll can hold up to 50 kg. LePage No More Nails mounting tape is waterproof and has high resistance to UV light, plasticizers and aging.

## RECOMMENDED FOR:

Applications on tiles, metal, wood, stone, glass and plastics including PVC, polyethylene, polypropylene and Nylon®. Ideal for mounting skirting boards, pictures, mailboxes, house numbers, hooks and auto trim attachments.

## NOT RECOMMENDED FOR:

- Teflon® surfaces.
- Contact with silicone
- Water immersion

## FEATURES & BENEFITS:

Feature	Benefits
Water resistant.....	Indoor and outdoor use
Fast and clean.....	Easy-to-use, no mess
Resistant to UV light and aging.....	Long outdoor life
Super strong.....	Holds up to 50 kg per roll

## COVERAGE:

1.5 m roll can hold up to 50 kg (or 5 kg for every 15 cm of tape).

## DIRECTIONS:

### Tools Typically Required:

Scissors or knife

### Preparation:

Use above 10°C (50°F). Surfaces must be clean, dry and free of frost, grease, dust and other contaminants. Clean surfaces with acetone or rubbing alcohol.

### Application:

Apply mounting strip to the object, remove protective red strip and press firmly on the target. On a large surface area, apply strips vertically. The position of the object cannot be corrected after pressing. Touching the tape with fingers during application should be avoided as the grease on the fingers can lead to a decrease in adhesive strength. Gap-filling properties of the tape are limited to the thickness of the tape. Initial tack of the tape is very high but final strength of the bonding is reached after 24 hours. Application of the tapes can damage delicate surfaces. Test before use.

## STORAGE AND DISPOSAL

Not damaged by freezing. Dispose of unwanted tape with trash.

## PRECAUTIONS

Refer to the Material Safety Data Sheet (MSDS) for further information

## DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

## TECHNICAL DATA

Typical Physical Properties:		Typical Application Properties	
<u>Colour:</u>	Translucent	<u>Application Temperature:</u>	Apply above 10°C (50°F)
<u>Appearance:</u>	Tape 19 mm wide x 1.14 mm thick	<u>Temperature Resistance:</u>	-40°C to 120°C (-40°F to 248°F)
<u>Base:</u>	Acrylic	<u>Tensile Strength:</u> (ASTM D412 die C):	140 N/cm <sup>2</sup> (203 psi)
<u>Shelf Life:</u>	24 months at 23°C and 50% relative humidity	<u>Elongation:</u> (ASTM D412 die C)	500 %
		<u>Peel Adhesion:</u> (ASTM D3330)	18 N/cm (10.3 lb/in)
		<u>Cleavage Peel Strength:</u> (ASTM D1062)	21 N/cm <sup>2</sup> (30.5 psi)
		<u>Dynamic Shear Strength:</u> (ASTM D3163)	63 N/cm <sup>2</sup> (91.4 psi)
		<u>Final Strength:</u>	24 hours