

Project:		Type:
		7F -
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LED PL LAMPS

5 CCT SELECTABLE

ORDERING INFORMATION

Order code:

PLH/S2/6W/5CCT/GX23/ND/STD Model number:

UPC: 069549028142

Inner box quantity: 10

PHYSICAL DATA

GX23 PL Horizontal Shape:

PERFORMANCE DATA

Watts (W): 6 Traditional equivalent (W) 13 Volts (VAC): 120-277

Color temperature (K)1: 2 700/3 000/3 500/4 000/5 000

Lumen output (Im)2: 550/575/600/625/625 Efficacy (Im/W): 92/96/100/104/104

CRI: 50 000 Life L70 (h)3: Beam angle (°): 120 0.96 Power factor: Frequency (Hz): 50-60 Ballast bypass Starting method:

Operating temp. range: Open Fixture: -20 °C to 35 °C (-4 °F to 95 °F)

Enclosed Fixture: -20 °C to 25 °C (-4 °F to 77 °F)


Application (Indoor/Outdoor):


¹ Typical color temperature range: +/- 5 %.

**Zumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

**3 Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

DIMENSIONS



















This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.